



<b>Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate</b>	<b>Licence Number</b>	<b>011-7S2462 R</b>
	Issued	19.11.2015

<b>Annual collector output kWh/module</b>														
<b>Collector name</b>	Location and collector temperature (T <sub>m</sub> )													
	Athens			Davos			Stockholm			Würzburg				
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
Buderus Logasol SKR10 CPC, 2 Module	2 398	2 156	1 830	2 070	1 789	1 465	1 503	1 279	1 026	1 613	1 378	1 107		

<b>Collector mounting: Fixed or tracking</b>	<b>Fixed; slope = latitude - 15° (rounded to nearest 5°)</b>
--	--

<b>Overview of locations</b>				
Location	Latitude °	G <sub>tot</sub> kWh/m <sup>2</sup>	T <sub>a</sub> °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

G <sub>tot</sub>	Annual total irradiation on collector plane	kWh/m <sup>2</sup>
T <sub>a</sub>	Mean annual ambient air temperature	°C
T <sub>m</sub>	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (T<sub>m</sub>). A detailed description of the calculations is available at <http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx>.